## A series 1.5t Mini Walkie Pallet Truck Specification:

	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.
Distinguishing mark	1.2	Manufacturer's type designation		CBD15-A3MC1-I
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker		Pedestrian
	1.5	Rated capacity/rated load	Q (kg)	1500
	1.6	Load centre distance	c (mm)	600
	1.8	Load distance, centre of drive axle to fork	. ,	
			x (mm)	950
	1.9	Wheelbase	y (mm)	1225
Weight	2.1	Service Weight(Including battery)	kg	180
Tyres, chassis	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane		PU
	3.2	Tyre size, front		Ф210x70
	3.3	Tyre size, rear		2×Φ80x64
	3.4	Additional wheel (dimensions)		1
	3.5	Wheels, number front / rear (x = driven wheels)		1x/4
	3.6	Tread, front	b10 (mm)	/
	3.7	Tread, rear	b11 (mm)	400
Dimensions	4.4	Lift	h₃ (mm)	120
	4.15	Fork height,lowered	h13 (mm)	80
	4.19	Overall length	lı (mm)	1669
	4.21	Overall width	bı(mm)	568
	4.22	Fork dimensions	s/e/l (mm)	50/160/1150
	4.25	Distance between fork-arms	bs (mm)	560/680
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	30
	4.35	Turning radius	Wa (mm)	1400 <sup>1)</sup>
Performance data	5.1	Travel speed,laden/unladen	km/h	4.5/4.9
	5.2	Lift speed,laden/unladen	m/s	0.05/0.06
	5.3	Lowering speed,laden/unladen	m/s	0.04/0.045
	5.8	Max Gradeability,laden/unladen	%	6/15
Electric	6.1	Drive motor rating S2 60 min	kW	0.65
	6.2	Lift motor rating at S3 15%	kW	0.8
	6.4	Battery voltage,rated capacity	V/Ah	24/40
	8.1	Type of drive control		DC
	9.1	Manufacturer		Curtis

Note: 1). When fork lowered,+60mm



