

Quad-Circuit Heavy-Duty

Hydraulica 2600 Quad-Circuit Compact [2600kg]

Bringing the latest in modern vacuum lifting technology to the market, the Hydraulica 2600 Quad-Circuit Compact boasts **four independent vacuum circuits** for quicker, safer and more efficient lifting performance on site.

Retaining all the benefits of our standard Hydraulica 2500 lifter, the innovative Hydraulica Quad-Circuit also has a more compact frame for fitting glass under tricky soffits and overhangs, as well as larger 520mm vacuum pads to achieve quicker vacuum suction. Features 210° powered rotation and 90° hydraulic tilt for easy control of heavy loads.

Key Features

- Capacity: 2600kg
- Four vacuum circuits with 4 on-board maintenance free vacuum pumps
- Powered 210° lockable rotation
- 90° hydraulic tilting
- Audio-visual low vacuum alert
- 12v rechargeable battery with integral 110v or 240v charger and battery energy gauge
- Wheeled stand for transport and storage available
- Cable remote control as standard, optional radio remote
- Individual pads can be isolated for irregular units
- Sliding extension arms

Reference Code

VGL62

Control panel with quad-circuit vacuum and 90° twin hydraulic tilt cylinder system



Wheeled stand as standard



Cable remote control as standard


Optional radio remote

Technical Specifications

Safe working load (smooth, clean surface at 60% vacuum)	capacity:	2600kg*	1850kg
Number of suction cups	cups:	12	8
Suction cup	description:	black rubber, not abrasion resistant, heat resistant up to 100°F	
Suction cup diameter	diameter:	520mm	
Suitable for lifting	material properties:	gastight / non-porous	
	surface:	smooth	
	example:	glass, plastic boards, ceramic plates, sheet metals, coated boards	
Weight of lifter	approx:	640kg (with 12 pads)	
Depth of lifter	depth::	385mm	
Rotation	rotation:	105° left & right powered hydraulic	
Tilt	tilt:	90° hydraulic	
Vacuum system	dual circuit:	4 pumps, 4 vacuum reserve tanks	
Voltage	pump:	12v DC from rechargeable batteries (2 in total)	
	battery charger:	110v/240v 50/60Hz single phase factory selectable	
Standard accessories	standard:	cable remote control, extension arms, wheeled stand	
Optional accessories	optional:	radio remote control	

* The capacity is 2600kg with extension arms and 12 pads fitted.

High Capacity
520mm Pads



Technical Data (mm)

